

Universal Protection - GPN 610


Virgin material



Material: PE-LD

Standard colour: yellow

Functional dimensions:



Dimension	A	B	C	D	E	G	H	Article number
GPN 610 U 1 LDPE sulphur yellow	10	4,4	6,2	4,6	2,8	10,8	10	610 0001 0000
GPN 610 U 2 LDPE sulphur yellow	11	6	7,8	6,2	4,4	10,8	10	610 0002 0000
GPN 610 U 3 LDPE sulphur yellow	13	7,6	9,4	7,8	6	10	10	610 0003 0000
GPN 610 U 4 LDPE sulphur yellow	14	8,4	10,2	8,6	6,8	10	10	610 0004 0000
GPN 610 U 5 LDPE sulphur yellow	14	9,2	11	9,3	7,5	10	10	610 0005 0000
GPN 610 U 6 LDPE sulphur yellow	15	9,9	11,7	10,1	8,3	10	10	610 0006 0000
GPN 610 U 7 LDPE sulphur yellow	16	10,6	12,4	10,8	9	10	10	610 0007 0000
GPN 610 U 8 LDPE sulphur yellow	17	11,3	13,1	11,2	9,5	10	10	610 0008 0000
GPN 610 U 9 LDPE sulphur yellow	18	12,2	14,1	12,5	10,4	12	12	610 0009 0000
GPN 610 U 10 LDPE sulphur yellow	18	12,5	14,6	13,3	11,2	12	12	610 0010 0000
GPN 610 U 11 LDPE sulphur yellow	19	13,5	15,6	14	11,9	12	12	610 0011 0000
GPN 610 U 12 LDPE sulphur yellow	19	14	16,1	14,5	12,4	12	12	610 0012 0000
GPN 610 U 13 LDPE sulphur yellow	21	15	17	15,5	13,2	13	13	610 0013 0000
GPN 610 U 14 LDPE sulphur yellow	22	16,3	18,6	17	14,7	13	13	610 0014 0000
GPN 610 U 15 LDPE sulphur yellow	22	17,3	19,4	17,6	15,5	13	13	610 0015 0000
GPN 610 U 16 LDPE sulphur yellow	24	17,5	20,1	18,5	15,9	15	15	610 0016 0000
GPN 610 U 17 LDPE sulphur yellow	25	18,4	21	19,4	16,8	15	15	610 0017 0000
GPN 610 U 18 LDPE sulphur yellow	25	19	21,6	20	17,4	15	15	610 0018 0000
GPN 610 U 19 LDPE sulphur yellow	27	20,4	23,2	21,6	18,8	16	16	610 0019 0000
GPN 610 U 20 LDPE sulphur yellow	28	20,7	23,5	21,9	19,1	16	16	610 0020 0000
GPN 610 U 21 LDPE sulphur yellow	29	22,2	24,8	23	20,4	16	16	610 0021 0000
GPN 610 U 22 LDPE sulphur yellow	30	23,2	26,3	24,4	21,2	18	18	610 0022 0000
GPN 610 U 23 LDPE sulphur yellow	32	24,5	27,8	26,2	22,9	19	19	610 0023 0000
GPN 610 U 24 LDPE sulphur yellow	33	25,5	29,2	27,7	23,7	19	19	610 0024 0000
GPN 610 U 241 LDPE sulphur yellow	33	26,4	30,4	28,9	24,9	19	19	610 0241 0000
GPN 610 U 25 LDPE sulphur yellow	35	27,8	31,1	29,5	26,2	19	19	610 0025 0000
GPN 610 U 26 LDPE sulphur yellow	37	29,8	32,6	31,1	28,3	16	16	610 0026 0000
GPN 610 U 27 LDPE sulphur yellow	38	31,4	35,1	32,8	29,7	21	21	610 0027 0000
GPN 610 U 28 LDPE sulphur yellow	41	33,3	37,1	35,5	31,7	22	22	610 0028 0000
GPN 610 U 29 LDPE sulphur yellow	45	36,7	40,5	39	35,2	22	22	610 0029 0000
GPN 610 U 291 LDPE sulphur yellow	45	38,4	40,7	39,2	36,9	13	13	610 0291 0000
GPN 610 U 30 LDPE sulphur yellow	48	38,2	43	41,4	36,6	23	23	610 0030 0000
GPN 610 U 31 LDPE sulphur yellow	48	39,6	42,9	41,3	38	19	19	610 0031 0000
GPN 610 U 32 LDPE sulphur yellow	49	41,4	44,7	43	39,7	19	19	610 0032 0000
GPN 610 U 33 LDPE sulphur yellow	51	44,4	47,7	46,1	42,8	19	19	610 0033 0000
GPN 610 U 34 LDPE sulphur yellow	54	45,2	49,6	48	43,6	25	25	610 0034 0000
GPN 610 U 35 LDPE sulphur yellow	55	46,6	51	48,7	45,2	25	25	610 0035 0000
GPN 610 U 36 LDPE sulphur yellow	62	52,5	56,9	55,2	50,8	25	25	610 0036 0000

GPN 610 U 37 LDPE sulphur yellow	65	54	59,3	57,8	52,5	25	25	610 0037 0000
GPN 610 U 38 LDPE sulphur yellow	65	54,2	58,6	57	52,6	25	25	610 0038 0000
GPN 610 U 39 LDPE sulphur yellow	67	58,8	62,8	61,1	56,7	25	25	610 0039 0000
GPN 610 U 40 LDPE sulphur yellow	71	60,7	67,1	64,3	57,5	28,5	29	610 0040 0000
GPN 610 U 41 LDPE sulphur yellow	75	67,1	70,4	68,7	65,4	19	19	610 0041 0000
GPN 610 U 42 LDPE sulphur yellow	83	72,4	75,7	74,1	70,8	19	19	610 0042 0000
GPN 610 U 43 LDPE sulphur yellow	92	84,5	87,8	85	82,4	18,5	19	610 0043 0000

Dimensions in mm Information on materials, colours, drawings and use of our articles can be found on pages 166/167. This application table represents guide values. We will be happy to send you free trial samples. For bolts, pins and tube ends please select according to the functional dimensions D and E. This application table is a guide. We will be happy to send you free test samples. For openings and bores without threads, please select according to functional dimensions B and C.

Our product advantages at a glance:



Vielseitiger.

Universell einsetzbar als Stopfen oder Kappe. Die Konizität eignet sich bestens zur Überbrückung von Toleranzen.



Sauberer.

Produktion nach VDA Band 19 und ISO 16232 im speziell eingerichteten Sauberraum auf Anfrage möglich.



Besser.

Zum Verschließen von Bohrungen und Innengewinden oder zum Schutz von Bolzen und Außengewinden.

The following products might also interest you:



GPN 615